Modular Cooking Range Line 900XP Two Wells Gas Fryer 23 liter

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA#		



Modular Cooking Range Line

900XP Two Wells Gas Fryer 23 liter

391080 (E9FRGH2JF0)

23+23-lt gas fryer with 2 "V" shaped wells (external burners) and 4 half size baskets

Short Form Specification

Item No.

High efficiency 40 kW burners in stainless steel. Suitable for natural gas or LPG. Deep drawn V-Shaped wells. Oil drains through a tap into a container positioned under the well. Height adjustable feet in stainless steel. Exterior panels in stainless steel. Worktop in 20/10, stainless steel. Rightangled side edges eliminate gaps and possible dirt traps between units

Main Features

- Deep drawn V-Shaped wells.
- High efficiency 40 kW burners in stainless steel with flame failure device attached to the outside of the well.
- Thermostatic regulation of oil temperature up to a maximum of 190 °C.
- Flame failure device on each burner.
- Overheat protection thermostat as standard on all units.
- Oil drains through a tap into a drainage container positioned under the well.
- All major compartments located in front of unit for ease of maintenance.
- Piezo spark ignition for added safety.
- IPX5 water resistance certification.
- The special design of the control knob system guarantees against water infiltration.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).
- Supplied as standard with 4 half size baskets and 1 right and left side doors for cupboard.

Construction

- Unit is 930 mm deep to give a larger working surface area.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Interior of well with rounded corners for ease of cleaning.

Modular Cooking Range Line 900XP Two Wells Gas Fryer 23 liter



Modular Cooking Range Line 900XP Two Wells Gas Fryer 23 liter

Included Accessories

• 2 of Door for open base cupboard PNC 206350 • 2 of 2 half size baskets for 18/23 lt fryers PNC 927223

Optional Accessories

• Junction sealing kit PNC 206086 PNC 206132 • Draught diverter, 150 mm diameter

 Matching ring for flue condenser, 150 mm diameter

• Kit 4 wheels - 2 swivelling with brake - it PNC 206135 is mandatory to install base support and wheels

PNC 206133

• Flanged feet kit PNC 206136

 Sediment tray for 6 gallon (23 lt) or 40 lb PNC 206173 frvers

Pair of side kicking strips (not for refr-PNC 206180 freezer base)

PNC 206201 Hygienic lid for 23lt fryers

• Frontal kicking strip for 23lt fryers in two PNC 206203 parts

Extension pipe for oil drainage for fryers PNC 206209

• Flue condenser for 1 module, 150 mm PNC 206246

diameter Water column with swivel arm (water PNC 206289

column extension not included)

• Chimney upstand, 800mm PNC 206304

• Door for open base cupboard PNC 206350

• Filter for fryer oil collection basin for 15lt, PNC 206359

18lt, 23lt free standing fryers • Base support for feet or wheels (lateral) PNC 206372 for 23lt fryers, pastacookers (900XP)

and refrigerated bases

PNC 206400 Chimney grid net, 400mm (700XP/900)

• Side handrail-right/left hand (900XP) PNC 216044

• Frontal handrail, 800mm PNC 216047

PNC 216049 • Frontal handrail, 1200mm

PNC 216050 • Frontal handrail, 1600mm

• 2 side covering panels for free standing PNC 216134 🗆 appliances

Large handrail - portioning shelf, PNC 216185 🗆 400mm

PNC 216186 🗆 · Large handrail - portioning shelf, 800mm

2 half baskets for 18/23lt fryers with front PNC 927200

hook 1 full basket for 18/23lt fryers with front PNC 927201

hook 2 half size baskets for 18/23 lt fryers PNC 927223

• Pressure regulator for gas units PNC 927225


• 1 full size basket for 18/23 It fryers PNC 927226


- Unclogging rod for 23lt fryers drainage pipe PNC 927227 □
- Deflector for floured products for 23lt fryers PNC 960645






Modular Cooking Range Line 900XP Two Wells Gas Fryer 23 liter





EQ = Equipotential screw

G = Gas connection



Gas

Gas Power:

391080 (E9FRGH2JF0) 136360 Btu/hr (40 kW)

Standard gas delivery:Natural GasGas Type Option:LPG;Natural Gas

Gas Inlet: 1/2"

Key Information:

Usable well dimensions (width):

340 mm

Usable well dimensions (height):

575 mm

Usable well dimensions

Well capacity:

400 mm

(depth):

21 It MIN; 23 It MAX

Thermostat Range: 120 °C MIN; 190 °C MAX

Net weight:115 kgShipping weight:130 kgShipping height:1080 mmShipping width:1020 mmShipping depth:860 mmShipping volume:0.95 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat

insulation fitted.

