Libero Line Series Induction, 2 zones, side by side

ITEM #	
MODEL #	
NAME #	
SIS #	
ΔΙΔ #	



Libero Line Series

Induction, 2 zones, side by side

600305 (DBPW4555)

Plug-in Induction cook top. 2 zones, side-by-side model

Short Form Specification

Item No.

Table top design, side-by-side model. Heavy duty 304 AISI stainless steel construction. High impact, heavy duty glass ceramic cooking surface for durability and easy cleaning. Two induction cooking zones (1,8kW each) with independent touch button controls. Automatic pan detection transfers power only when the pan is present, maximizing energy efficiency. No heat emission into the work environment only to the magnetic induction pans. Smooth rounded edges guarantee a flush fit between units. Digital power level display and touch button control panel. IP24 protection. Cord and plug included.

Main Features

- Table top design, side by side model.
- Heavy duty AISI 304 Stainless stee construction.
- Sealed heavy duty glass-ceramic cooking surface, 4 mm in thickness.
- Two independently controlled induction cooking zones with touch button control panel.
- Digital power level display.
- Automatic pan detection to transfer power only when pan is present.
- Rapid heat trasfer directly to the pan, no heat is dispersed into the environment.
- IP24 protected.
- Cord and plug included.
- 4 adjustable feet.
- Suitable for pot and pan with diameter of 140-250mm.

Optional Accessories

- Stainless steel universal frying pan with stainless steel handle (diam. 200mm) suitable for induction and all other heating sources
- Universal frying pan with stainless steel handle (diam. 240mm) suitable for induction and all other heating sources
- Universal frying pan with stainless steel handle (diam. 280mm) suitable for induction and all other heating sources
- Universal frying pan with smooth PNC plate suitable for induction 653617 ☐ cookers
- Universal frying pan with ribbed PNC plate suitable for induction 653618 ☐ cookers

APPROVAL:



Libero Line Series Induction, 2 zones, side by side

Electric

Supply voltage:

600305 (DBPW4555) 230 V/1N ph/50/60 Hz

Total Watts: 3.6 kW

Minimum Circuit Ampacity

(MCA): 16A

Key Information:

Front Plates Power: 1.8 - 1.8 kW
External dimensions, Height: 135 mm
External dimensions, Width: 600 mm
External dimensions, Depth: 325 mm
Net weight: 12 kg

1phase: Schuko; 3phase:

Plug Type: CEE

