



Electrolux

Water Treatment External manual water softener, 20lt

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



Electrolux

Water Treatment
External manual water softener, 20lt



Water Treatment

External manual water softener, 20lt

860430 (WTAC22)

20lt external manual water softener

Short Form Specification

Item No. _____

Designed specifically for single tank dishwashers such as undercounter, glasswasher and hood type models.

Routine regeneration is recommended to suit the use of water softener and the hardness of the water used.

Operating pressure between 1 and 8 bar.

Incorporates 12-litre cylinder in stainless steel 304 AISI.

Flow rate 1000l/h.

Every regeneration cycle requires 1,5kg of salt.

Water connection between 5°C to 15°C.

Main Features

- Operating pressure between 1 and 8 bars.
- Every regeneration cycle requires 1,5 kg of salt.
- Water connection between 4°C and 15°C.
- Quantity of soft water depending on supply water hardness:
 - 30°F (16,5°d) - 3000lt
 - 40°F (22°d) - 2000lt
 - 60°F (33°d) - 2100lt
 - 80°F (44°d) - 1500lt

Construction

- Incorporates 2 litre cylinder in stainless steel 304 AISI.
- Flow rate 1000 l/h.

APPROVAL: _____

Key Information:**External dimensions, Height:****860430 (WTAC22)** 900 mm**External dimensions, Width:** 190 mm**External dimensions, Depth:** 190 mm**Net weight:** 19 kg**Shipping height:** 39 3/8" (950 mm)**Packaging size
(WxDxH):** 190x190x900 mm